

## Aeromax 6 floor standing speaker

- BMR (Balanced Mode radiator) driver to seamlessly cover the frequency range from 250Hz to 22kHz, allowing the woofers to be entirely optimised for efficient bass response, effectively becoming dedicated subwoofers
- Twin sub-bass drivers are perfectly optimized to produce deep and powerful bass
- 4<sup>th</sup> Generation BMR driver with exceptional high frequency extension to bring crisp top end
- Ultra high grade crossover components to bring superb levels of detail and transparency
- Extensively braced cabinets that lock the drive units mechanically to the cabinet structure resulting in lower colouration and cleaner dynamics
- OFC internal cabling for the purest signal path from the audiophile grade, gold plated terminal posts to the crossover and drive units
- Available in gloss white and gloss black finishes



## Detailed Specifications

<b>Sensitivity</b>	90dB
<b>Frequency response</b>	30Hz – 22kHz
<b>Impedance</b>	8 Ohms compatible
<b>Recommended amplifier power</b>	25-120 Watts
<b>Drivers</b>	1 x 46mm (2") BMR 2 x 165mm (6.5") high power subwoofers
<b>Ported</b>	1 front
<b>Colour</b>	Gloss Black or White
<b>Dimensions (H x W x D)</b>	980 x 240 x 344mm (38.6 x 9.4 x 13.5") including grille & plinth
<b>Weight</b>	17kg (37.4lbs) each



Aeromax 6 floor standing speaker